Prepared By:



Maximum Predicted Water Table And Hydrogeological
Assessment Report
Proposed Class "A" Pit Above Water
JT Pit

382063 Concession 4, Bentinck Municipality of West Grey JT Excavating Ltd.

GMBP File: 220135

Revised November 2023





TABLE OF CONTENTS

1.	INIR	ODUCTION	1
2.	METI	HODOLOGY	1
2.	1 E	Background Data Collection/Review	1
2.:	2 F	Field Investigations	2
	2.2.1	Monitoring Well Installations and Water Level Monitoring	2
3.	REVI	EW OF BACKGROUND INFORMATION	2
3.	1 F	Physiography and Geology	2
3.	2 (Conservation Authority and Screening Areas	3
3.	3 F	lydrogeology	3
4.	FIELI	D INVESTIGATIONS	4
4.		Nonitoring Well and Piezometer Installations	
5 .	ESTI	MATED WATER TABLE ELEVATION	5
6.	IMPA	CT ASSESSMENT	5
6.	1 I	mpacts to Local Groundwater and Groundwater Resources	5
6.	2 N	Aunicipal Wells	7
	6.2.1	Municipal Wells - Regulatory Setting	7
6.	3 F	Potential Interference with Surface Water Resources	8
	6.3.1	Seasonally Saturated and Ponding Areas	8
	6.3.2	Saugeen River and Flood Plain	8
	6.3.3	Surface Water – Quality	9
	6.3.4	Surface Water- Quantity	10
7.	SUM	MARY OF FINDINGS	10
8.	QUA	LIFICATIONS OF ASSESSORS	11

REVISED NOVEMBER 2023

GMBP FILE: 220135

LIST OF FIGURES

FIGURE 1: SITE LOCATION PLAN

FIGURE 2: MONITORING WELL LOCATION PLAN

FIGURE 3: GROUNDWATER FLOW PLAN

FIGURE 4: CROSS-SECTION A-A' FIGURE 5: CROSS-SECTION B-B'

FIGURE 6: MECP WELL LOCATION PLAN

LIST OF TABLES

TABLE 1: SUMMARY OF NEARBY WATER SUPPLY WELLS

TABLE 2: ONSITE GROUNDWATER ELEVATIONS

APPENDICES

APPENDIX A: MOECC WELL RECORDS

APPENDIX B: BOREHOLE LOGS
APPENDIX C: SITE PHOTOGRAPHS

APPENDIX D: SAUGEEN VALLEY CONSERVATION AUTHORITY MAPPING

APPENDIX E: GREY COUNTY OFFICIAL PLAN MAPPING AND INFORMATION



MAXIMUM PREDICTED WATER TABLE AND HYDROGEOLOGICAL ASSESSMENT REPORT

PROPOSED CLASS 'A' PIT ABOVE WATER

REVISED NOVEMBER 2023

GMBP FILE: 220135

1. INTRODUCTION

GM BluePlan Engineering Limited (GMBP) was retained by JT Excavating Ltd. to conduct a Hydrogeological Assessment to support the application for a proposed Category 3, Class "A" Pit above water. The proposed Aggregate Pit is situated on the north side of Concession Road 4, Bentick approximately 9.5 km northeast of the Town of Hanover. The property is located on Lot 22, Concession 5 in the former Township of Bentinck, Municipality of West Grey. The civic address of the subject property is 382063 Concession Road 4, Bentinck. The location of the Site is shown on Figure 1.

This Level 1 Hydrogeological Study is being prepared to characterize the geology, the potential groundwater occurrence, and the elevation of the water table within the proposed extraction area in order to support development and licensing under the Aggregate Resources Act (ARA). Additionally, this Study investigates the potential adverse impacts that the proposed pit may have on the local groundwater and surface water resources in the area. It is our understanding that the proposed pit operations will be conducted to a maximum depth of 1.5 metres above the "high" groundwater table elevation.

The subject property encompasses approximately 41.2 ha (102 acres) and is used primarily for agricultural purposes. The property consists of agricultural fields consisting of crops and naturalized treed and vegetated areas. The northern portion of the property contains an auxiliary building inferred to be used for agricultural purposes and/or storage. A low-lying vegetated area with seasonal saturation/ponding was observed to extend in an east-west direction across the central portion of the Site, which effectively separates the southern fields with the northern field. Additionally, the northernmost portion of the property is at a relatively low elevation compared to the majority of the Site and is currently undeveloped and vegetated. The Site boundaries and features are shown on Figure 2.

2. METHODOLOGY

2.1 Background Data Collection/Review

Available information from the following sources was reviewed to support the site-specific information gathered from field investigations to prepare the hydrogeological assessment:

- Ministry of the Environment Conservation and Parks (MECP) well records.
- MECP publications, geologic publications,
- Review of the Grey and Bruce Counties Groundwater Study (Waterloo Hydrogeologic, July 2003), and pertinent maps

GMBP FILE: 220135
REVISED NOVEMBER 2023

 Review of the Municipal Water Supply Wellhead Protection Areas (WHPAs) established through the Grey and Bruce Counties Groundwater Study, completed in July 2003 and prepared by Waterloo Hydrogeologic Inc.

2.2 Field Investigations

2.2.1 Monitoring Well Installations and Water Level Monitoring

In order to provide more certainty regarding the on-site groundwater elevations and flow direction, a series of four (4) monitoring wells were installed between February 22 and 23, 2021. The monitoring wells were advanced by London Soil Test Limited (LST) with a track-mounted drill, under the direction of GMBP, to depths of between 4.6 and 8.7 mbgs. Borehole logs are provided in Appendix B.

These monitoring wells and piezometers are used to measure the groundwater elevations and determine the "high" water levels associated with the property. The water levels at each of the monitoring locations were measured by GMBP personnel during a total of four (4) site visits between February 23, 2021 and March 25, 2022.

During the site visits, a review of the site conditions, including the surface topography, natural features, surface water features, and the characteristics of the neighboring properties (i.e. surrounding land use) were noted. In addition, the potential for the presence of springs or groundwater seeps was investigated.

On March 22, 2021, the monitoring well elevations and various topographical elevations were surveyed by GMBP using a GPS and total station survey system in order to provide elevation and spatial data.

3. REVIEW OF BACKGROUND INFORMATION

3.1 Physiography and Geology

Based on our review, the site is located within the physiographic region of the Horseshoe Moraines. In general, the Horseshoe Moraines are characterized by drumlinized till plains, kame moraines, and outwash deposits (Chapman and Putnam, 1984).

The soils on and surrounding the subject site are identified as that of the Sargent series, which is defined as a series of two thin layers of grey and brown loam (i.e. ~0.10 metres each) overlying well-sorted gravelly outwash deposits (Soil Survey Report No. 17). The physiographic mapping (Map 2225) indicates that the subject property is located in an area of glacial spillway deposits. According to the Surficial Geology of Southern Ontario (Ontario Geologic Survey), the subject property contains coarse textured glaciofluvial deposits consisting of river deposits and delta topset facies.

The Site is reported to be situated on or near the spatial contact between dolostone of the Guelph formation to the northeast and Salina formation to the southwest. Based on the mapping provided by the Grey and Bruce Groundwater Study, an analysis of water well logs in the area, the depth to bedrock in the vicinity of the subject property is reported to be in the range of 13 to 26 meters below ground surface (mbgs).

The subject Site primarily consists of gently undulating hills gradually sloping toward the west and the Saugeen River west of the Site. As discussed, a low-lying vegetated area with seasonal ponding was observed to extend in an east-west direction across the central portion of the Site, which effectively separates the southern fields with the northern field. Additionally, the northernmost portion of the property is at a relatively low elevation compared to the majority of the Site and is currently undeveloped and vegetated.





Based in onsite observations during the four Site visits in 2021 and 2022, the low-lying areas in the southwest and central portions of the Site were only saturated during the early spring freshet, when the groundwater elevations are at their maximum.

3.2 Conservation Authority and Screening Areas

The site is situated within the boundary of the Saugeen Valley Conservation Authority (SVCA). From a review of the site with respect to regulated areas, the following is noted:

- An approximate 30 metre buffer associated with the seasonally saturated areas on the property is considered to be a screening area under Ontario Regulation 169/06.
- The lower-lying southwestern and western portions of the Site are currently designated as SVCA screening areas (under Ontario Regulation 169/06) associated with the flood plain and associated setbacks from the Saugeen River.

The SVCA mapping is presented in Appendix "D".

Additionally, the Grey County Official Plan identifies a slightly smaller area than the noted SVCA screening area as *Hazard Lands*, as per Schedule "A" of the official plan, and are subject to the associated developmental restrictions. It is noted that this designation identifies lands that "can be impacted by flooding, erosion, and/or dynamic beach hazards or have poor drainage, or any other physical condition that is severe enough to pose a risk for the occupant, property damage, or social disruption if developed."

The Grey County Official Plan mapping is presented in Appendix "E".

3.3 Hydrogeology

The Grey and Bruce Counties Groundwater Study (Waterloo Hydrogeologic, 2003), existing water well logs, and observations during on-site drilling provide an overview of the regional setting and more general information about the site and the surrounding area. The pertinent findings are summarized as follows:

- The depth to bedrock in the area is estimated to be between 13 and 26 mbgs;
- The overburden thickness was observed to be greater than 8.7 metres thick in the location of each monitoring well installed on the Site;
- The water table elevation in the overburden has been measured to be between approximately 292.0 metres above mean sea level (masl) in the northeastern portion of the Site and 288.0 masl in the southwestern portion of the Site based on the March 25, 2022 measurements;
- The soils across the site were observed to generally consist of coarse sand and gravel deposits overlain by between 0.2 to 0.5 metres of topsoil. The exception is the lower-lying soils on the north portion of the Site (i.e. MW-1 area), which consists of a thin layer (i.e. approximately 0.3 m) of clay with trace silt overlying the coarse textured soil, and a 1.5 metre thick layer of clay that was observed between approximately 1.5 and 3.0 mbgs in the location of MW-4.

GMBP FILE: 220135 REVISED NOVEMBER 2023

 The seasonal ponding areas in the central portion of the Site are inferred to be associated with the shallow water table elevation due to the presence of coarse textured soils across the Site and the absence of a surface water inlet or outlet from these areas.

To confirm the site-specific geology, a review of the Ministry of the Environment (MECP) well records for the site and surrounding area was conducted. MECP records were utilized from the MECPs online database (last updated June 4, 2021). A copy of the pertinent MECP well records is enclosed in Appendix A and a summary of the results of the well search within a 500 m radius of the subject site is provided in Table 1.

Five (5) well records were found within the 500 m well search radius, including the onsite well. Each well location correlates with known residential/agricultural properties in the vicinity of the Site.

Shallow groundwater flow is expected to mimic topography and generally flows towards surface water features. Based on measured groundwater table elevations across the Site and the presence of the Saugeen River west of the property (flowing in a southerly direction), the water table is expected to decline in a southwesterly direction toward the Saugeen River. Consequently, the water table is expected to be lowest in the southwestern portion of the Site (i.e. approximately 288 masl).

The Saugeen River is expected to form a flow divide for shallow groundwater, such that flow from the west side of the river is expected to flow easterly, and flow from the east side of the river, to flow easterly.

The more regional, or bedrock flow patterns are expected to be generally in a west, to northwesterly direction, towards Lake Huron, and consistent with the trend of the overall catchment area.

4. FIELD INVESTIGATIONS

4.1 Monitoring Well and Piezometer Installations

As discussed, on February 22 and 23, 2021, a series of four (4) monitoring wells (MW-1 to MW-4) were installed across the subject property. Borehole logs, including monitoring well installation details, are provided in Appendix B.

The water levels at each of the monitoring locations were measured by GMBP personnel during a total of seven (7) site visits between February 23, 2021 and June 25, 2023. A summary of the water level elevations measured to date is provided in Table 2.

Based on the water level elevations measured, the localized groundwater flow direction across the site is observed to be in a southwesterly direction toward the Saugeen River. This is expected to be influenced by both the local topography and surface water features.

Based on field observations and groundwater elevation data collected, the occurrence of surface water on the Site (i.e. in the central saturated area) is expected to be consistent with the occurrence of the groundwater elevation. The highest measured elevation of the groundwater across the proposed extraction area of the Site is inferred to be between approximately 292.0 metres above mean sea level (masl) in the northeastern portion of the Site and 288.0 masl in the southwestern portion of the property based on the April 10, 2023 measurements.

GMBP FILE: 220135
REVISED NOVEMBER 2023

5. ESTIMATED WATER TABLE ELEVATION

Based on the geologic mapping, MECP well records, and Grey and Bruce Counties Groundwater Study, the high water table elevation in the area is generally estimated to be in the range of 292.0 to 288.0 masl, which corresponds to a water table between 1.0 and 13 metres below the ground surface. This is consistent with the water level elevations measured from the monitoring wells and surface water elevations across the Site and the relative difference in ground surface elevation between the lower-lying western portions of the Site and the elevated eastern portion of the property.

Based on the water level elevations measured, the localized major groundwater flow direction across the Site is to the southwest, influenced by the Saugeen River, which is situated approximately 260 metres west of the subject property at its closest point and flows in a southerly direction.

Based on the groundwater conditions, timing of the freshet, and precipitation events, the water level measurements collected, the "high" groundwater table elevations are expected to be consistent with the water levels measured on April 10, 2023 It is noted that these measurements were made following a period of significant snow melt and precipitation.

It is recommended that the monitoring wells continue to be monitored during the Pit Application process in order to ensure the collection of data that is reflective of the "high" water table elevation.

As discussed, in the portion of the site where extraction is proposed, the high water table is considered to decline from approximately 292.0 metres above mean sea level (masl) in the northeastern portion of the Site to approximately 288.0 masl in the southwestern portion of the property based on the April 10, 2023 measurements, as shown in Figure 3. Therefore, to maintain the 1.5 m separation, based on the proposed limits of onsite extraction, the maximum depth of the pit would be approximately 293.5 masl the northeast portion of the area of extraction and sloping to approximately 290.5 masl in the expected southwestern-most portion of the proposed extraction area. The expected "high" water table and corresponding proposed maximum pit depths are shown on the Figure 4A and 4B.

6. IMPACT ASSESSMENT

6.1 Impacts to Local Groundwater and Groundwater Resources

With respect to impacts to groundwater resources from development activities, these can often be separated into: 1) quality, or 2) quantity.

With respect to quality, potential changes to groundwater are not typically caused by excavation works above the water table.

The moving and stockpiling of native/existing soils may cause disruption at surface, but not typically the release of compounds to the subsurface. With respect to the on-site equipment, a potential for environmental impact may be associated with petroleum hydrocarbons (fuel) used on-site. Standard best management practices and standards under the Aggregate Resources Act require the implementation of a spill prevention and contingencies measures plan, mitigating this risk.



REVISED NOVEMBER 2023

GMBP FILE: 220135

With respect to quantity, the proposed bottom contours of the aggregate pit have been selected to prevent alteration to the groundwater flow regime. As discussed, the proposed bottom contours are a minimum of 1.5 metres above the estimated "high" water table elevation. Therefore, pit operations will not include dewatering or groundwater diversion. Thus, no impacts to groundwater are anticipated by mining aggregate above the water table. Groundwater will not be diverted or altered during the aggregate extraction process. The overall water budget, pre- to post-development, is expected to remain unchanged.

Regardless of the fact that impacts are not expected, a further investigation of potential receptors has been conducted as part of this assessment. A review of MECP well records for the site and surrounding area was conducted and indicated seven (7) wells within 500m of the subject property. Additionally, from a review of surrounding properties, it is expected that an additional six (6) properties would have domestic/livestock wells that are currently being used. Domestic/livestock wells not documented in the MECP water well database are expected to be located at the following addresses:

- 133873 Allan Park Road Located approximately 390 metres northwest of the property boundary west and across the Saugeen River from the Site;
- 133859 Allan Park Road Located approximate 370 metres west of the property boundary west and across the Saugeen River from the Site;
- 133776 Allan Park Road Located approximately 470 metres southwest of the property boundary west and across the Saugeen River from the Site;
- 382007 Concession Road 4 Located approximately 340 metres southwest of the property boundary west and across the Saugeen River from the Site;
- 382048 Concession Road 4 Located approximately 230 metres south of the property boundary across the Concession Road 4 Right-Of-Way (ROW) and adjacent to the east bank of the Saugeen River;
- 382064 Concession Road 4 Located approximately 380 metres south of the property boundary across the Concession Road 4 ROW.

Copies of the pertinent MECP well records are enclosed in Appendix A and a summary of the results of the well search within 500 m is provided as Table 1, which includes a summary of both the MECP well record locations as well as those properties inferred to have a domestic well.

Of the wells identified/inferred, only one of the domestic wells are located within 300 metres of the subject property:

• The inferred domestic well located at 382048 Concession Road 4 is in a hydraulically cross-gradient direction from the proposed area of extraction on the subject Site. The southernmost extraction activities are expected to be located in the range of 330 metres from the location of this this well due required setbacks from the Concession Road 4 ROW and the location of viable and accessible aggregate resources on the Site. Additionally, the significant majority of the extraction is expected to take place between 400 and 1,100 metres from this well. Therefore, the potential for adverse effects on the quality and quantity of groundwater within the well located at 382048 Concession Road 4 is expected to be insignificant.

The seven wells identified in the MECP database, and five of the six inferred domestic wells are reported/estimated to be situated between 320 and 500 metres from the subject property boundary.



GMBP FILE: 220135
REVISED NOVEMBER 2023

It is noted that the lands west and hydraulically downgradient of the subject property are largely undeveloped and are designated as Environmental Hazard Lands in the Grey County Official Plan and SVCA screening areas under Ontario Regulation 169/06. These development limitations are associated with the inferred 100 year flood levels of the Saugeen River. As such, any developed properties west and hydraulically downgradient of the Site are across, and hydraulically separated by, the Saugeen River.

More specifically, of the fifteen wells identified/inferred within 500 metres of the property boundary, only four are not across the Saugeen River / hydraulically separated from the Site. Each of these four wells are located in areas that are either hydraulically upgradient or cross-gradient from the Site. Therefore, the potential for adverse effects on the quality and quantity of groundwater within the wells identified within 500 metres of the Site is expected to be insignificant.

In summary, MECP well records indicate that there seven well records within a 500 m radius of the property. Six additional wells have been inferred to exist based on the presence of developed properties. Based on the proposed extraction above the water table elevation and the fact that water quality is not expected to be altered due to proposed operations, it is reasonable to expect that the proposed aggregate extraction would not impact the groundwater supply resources in the area. Based on the separation distance of the expected limit of extraction from the domestic wells (i.e., greater than 330 m), the shallow groundwater flow towards the Saugeen River, and the hydraulic separation between the Site and the majority of the identified domestic supply wells within 500 metres of the Site via the Saugeen River, the potential for impacts to off-site domestic wells is further mitigated.

6.2 Municipal Wells

6.2.1 Municipal Wells - Regulatory Setting

The Clean Water Act (CWA) was established in 2006 to protect and to ensure the quality and sustainability of municipal supplies of drinking water sources within the province. A focus of the CWA is the preparation of locally developed source protection plans and vulnerability assessments which can then be used to identify threats to the municipal wells. Under the CWA, a drinking water threat is defined as an activity or condition that adversely affects or has the potential to adversely affect the quality or quantity of any water that is or may be used as a source of drinking water, and includes an activity or condition that is prescribed by the regulations as a drinking water threat.

Based on a review of mapping, the site is not located within a regulated area, such as well head protection zone or intake protection zone. The nearest areas regulated under the CWA are located greater than 10.0 km away and would have no bearing on this development.

REVISED NOVEMBER 2023

GMBP FILE: 220135

6.3 Potential Interference with Surface Water Resources

6.3.1 Seasonally Saturated and Ponding Areas

As discussed, a seasonally saturated area is situated in the central portion of the property. Due to the coarse-textured nature of the soils onsite, this feature is expected to be consistent with the occurrence of water table elevation. More specifically, since this area was observed to be dry during the June 30, 2021 Site visit, it is expected that water is only present in this area during relatively high groundwater conditions or during surface run-off flooding events. The locations of these features are shown in Appendix "D" and "E".

Further, the western portion of the property is currently designated as Hazard Lands and an Ontario Regulation 169/06 screening area. These limitations on the Site development are associated with the floodplains of the Saugeen River, located approximately 160 metres west of the subject property at its closest point.

The proposed onsite pit operations are required to have a setback from the areas of the property designated as Hazard Lands as part of the Grey County Official Plan. It is noted that the SVCA regulated screening area extends 50 metres beyond the noted Hazard Land boundary. It is our understanding that development within the area designated as an SVCA screening area is not prohibited as long as suitable consultation with the SVCA has been conducted and written permissions or permits (if required) have been obtained.

It is of particular note that the proposed operations are to be above the water table. No dewatering or water diversion will take place onsite as part of aggregate extraction operations. Based on the occurrence of coarse-grained soils (i.e., the sand and gravel) below the groundwater table, the pre- to post-development groundwater flows are expected remain similar. Consequently, the groundwater flow to the onsite seasonal surface water feature and more largely to the west toward the Saugeen River, considering both the water budget and flow direction, is expected to remain unchanged from pre-extraction to post-extraction when appropriate setback distances are maintained. Thus, no impacts to these areas are anticipated.

6.3.2 Saugeen River and Flood Plain

The Saugeen River is situated approximately 160 metres west of the subject property at its closest point, which flows in a southerly direction. The western portion of the property is currently designated as *Hazard Lands* and an Ontario Regulation 169/06 screening area. These limitations on the Site development are associated with the floodplains of the Saugeen River.

During the April 7 and June 30, 2021 Site visits, the western portion of the property was observed to be generally dry, with no evidence of surface water with the exception of the seasonally saturated / ponding area in the central portion of the Site discussed in Section 6.3.1 above, which was found to contain some standing surface water during the April 7, 2021 Site visit. As such, although the western portion of the Site is reported to fall within the GCOP *Hazard Land* and the SVCA Screening Area, the western portion of the Site does not show evidence of recent seasonal saturation and is expected to only become saturated during record snowmelt or storm events, which would cause the Saugeen River to flood to the limits of the designated floodplain of the river (i.e. 100 year flood event). Further, agricultural activities have been ongoing up to the western property boundary that do not appear to be hindered by saturated soil conditions.

Considering the proposed area of extraction is located outside of the designated *Hazard Lands* and the required setbacks will be implemented, no impacts to the Saugeen River or its flood plain are anticipated.

GMBP FILE: 220135 REVISED NOVEMBER 2023

6.3.3 Surface Water - Quality

As discussed, the area designated as seasonally ponding has been observed to only contain standing water during the period of high groundwater elevation (i.e. the spring freshet) and is noted the be dry during the remainder of the year. The Saugeen River is situated approximately 160 metres west of the property boundary at its closest point.

The proposed licensed area is expected to be located at least 30 metres from the lands designated as *Hazard Land* in the GCOP. As such, the SVCA screening area (effectively defined as a 30 metre buffer beyond the GCOP *Hazard* Lands) is not located within the proposed area of extraction.

Based on the required setback from both the boundary of the Saugeen River floodplain and the seasonally saturated pond area, as well as the implementation of best management practices for sediment and run-off control, no impacts to these surface water features are anticipated.

Based on the proposed pit activities, the primary quality concerns relate to the potential degradation of water quality through:

- Increased sediment/suspended solids loading, and
- Increased temperature.
 - With respect to increased sediment and/or turbidity, this is caused through mobilization of finegrained silt and clay sized soil particles (fines). In this particular scenario the following mechanisms will act to prevent fines:
- Only a small content of fines was encountered across the Site. Therefore, it is expected that very little fines will be mobilized during operations.
- The distance and low topographic relief between the pit activities and the Saugeen River will act as a buffer.

Potential impacts to water temperature are not considered to be an issue between pre- and post-development since:

- No surface water ponding is proposed/expected to occur in the proposed areas of extraction,
- Equal infiltration to the subsurface will continue post-development.

Based on proposed extraction to the water table, no water ponding (nor diversion) would occur. During aggregate pit development, precipitation would continue to infiltrate. As such, there is no increased potential for warming of groundwater recharging to the shallow system in the vicinity of the aggregate pit.

The Pit operations will include a spills response plan, which includes training for the proper and safe use, handling, and storage of fuel or other potential contaminants. All spills or releases of contaminants are to be reported immediately to the MECP Spills Action Centre. Further, a spills response plan will be posted onsite at all times.

REVISED NOVEMBER 2023

GMBP FILE: 220135

6.3.4 Surface Water- Quantity

The surface water quantity is expected to remain the same pre- and post-development since:

 the surface water features, including outlet elevations and controls, are not to be adjusted as part of the pit development,

To mitigate potential impacts to water quantity we recommend the following mitigative measure:

• To generally maintain surface water flows to the same low-lying locations, sloping of the restored grades to maintain similar catchment areas (pre- and post-development) shall be conducted.

7. SUMMARY OF FINDINGS

The purpose of this Maximum Predicted Water Table Elevation and Hydrogeological Assessment Report is to assess the hydrogeological information available in the vicinity of the subject property to characterize the geology, potential groundwater occurrence, and the inferred elevation of the water table within the proposed extraction area. Additionally, this study investigates the potential adverse Impacts the pit may have on the local groundwater and surface water resources in the area.

Based on the geologic mapping, MECP well records, Grey and Bruce Counties Groundwater Study, and on the site-specific investigations completed to date, it was observed that shallow groundwater flows in a generally west-southwest direction across the Site. More specifically, groundwater flows are influenced by topography and the Saugeen River. From these observations, based on the proposed pit above groundwater, the maximum elevation of the floor of the quarry would be controlled by the inferred high groundwater elevations.

Currently, the "high" water levels at the site have been estimated to be 292.0 masl the northeast portion of the property and sloping to approximately 288.0 masl in the expected southwestern-most portion of the property (i.e. MW-3). Therefore, to maintain the 1.5 m separation, and based on the proposed limits of onsite extraction, the maximum depth of the pit would be 293.5 masl the northeast portion of the property and sloping to 290.5 masl in the expected southwest portion of the proposed extraction area. As schedule permits, it is recommended that water levels continue to be measured during the application process so that direct measurement of the "high" water level can be confirmed, and the pit floor elevation be updated accordingly.

Based on the proposed extraction of aggregate to depths associated with the high water table elevation with no proposed dewatering or water diversion, and assuming that setback distances are maintained for the sensitive features of the property (as identified and recommended by the Natural Environment Technical Report), it is reasonable to expect that the proposed aggregate extraction would not impact the local water supply wells in the area, surface water features, or associated ecological receptors in the area.

Based on this review, the development standards developed under the ARA are considered to be sufficient to protect the local water resources.



REVISED NOVEMBER 2023

GMBP FILE: 220135

8. QUALIFICATIONS OF ASSESSORS

The Hydrogeological Investigation was completed by Mr. Corbin Sweet, H.B.Sc., P.Geo., and Mr. Matthew Nelson, P.Geo., P.Eng., M.Sc. of GMBP in consultation with applicant.

Mr. Corbin Sweet, H.B.Sc., P.Geo. has an honours B.Sc. degree in Earth Sciences (Geology) from the University of Waterloo and a diploma in Earth Resources from Sir Sandford Fleming College. He has over seven years of experience conducting numerous hydrogeological investigations and relevant public and agency consultation in support of pit and quarry ARA applications resulting in successful licences issued to applicants. He is also a member of the Professional Geoscientists of Ontario (PGO).

Mr. Matthew Nelson, P.Geo., P.Eng., M.Sc. is an Environmental Engineer / Hydrogeologist with over sixteen years of experience with hydrogeological investigations in support of pit and quarry ARA applications and associated consultation, resulting in successful licences issued to applicants. He is also a member of the Professional Geoscientists of Ontario (PGO) and Professional Engineers of Ontario (PEO).

All of which is respectfully submitted,

GM BLUEPLAN ENGINEERING LIMITED

Per:

C.J. Sweet, H.B.Sc., P.Geo.

My

CJS/kd

Per:

Matthew Nelson, M.Sc. P. Eng. P. Geo.

		FIGURES:





SCALE = 1:50,000 MARCH 2022

SITE LOCATION MAP





LEGEND

•

MONITORING WELL

ROPERTY BOUNDAR

XISTING GROUND SURFACE CONTOURS

Scale = 1:4,000 MARCH 2022

MONITORING WELL LOCATIONS





<u>LEGEND</u>

MONITORING WELL
PROPERTY BOUNDARY
GROUNDWATER CONTOURS
CROSS SECTION

GROUND SURFACE ELEVATION (mosl)


WATER LEVEL ELEVATION (mosl)

APPROXIMATE BOUNDARY OF
PROPOSED EXTRACTION

<u>Scale = 1:4,000</u> DECEMBER 2023

GROUNDWATER CONTOUR PLAN







SCREENED INTERVAL

GROUND SURFACE

____ INFERRED GROUNDWATER LEVEL

INFERRED HIGH GROUNDWATER ELEVATION (i.e. MAX. PROPOSED PIT DEPTH)

1.5m SEPARATION FROM

NOTE:

VERTICAL EXAGGERATION IS 10X

2. W.L.'S PRESENTED ARE
CONSIDERED TO BE THE
ANNUAL HIGH GROUNDWATER
ELEVATION (APRIL 10, 2023)


Horizontal Scale = 1:3,000

DECEMBER 2023

CROSS-SECTION A-A'

Figure No. 4A





LEGEND:

SCREENED INTERVAL

GROUND SURFACE

INFERRED

GROUNDWATER LEVEL

1.5m SEPARATION FROM

INFERRED HIGH GROUNDWATER ELEVATION (i.e. MAX. PROPOSED PIT DEPTH)

NOTE:

- 1. VERTICAL EXAGGERATION IS 10X
- 2. W.L.'S PRESENTED ARE
 CONSIDERED TO BE THE
 ANNUAL HIGH GROUNDWATER
 ELEVATION (MEASURED APRIL
 10, 2023)

Horizontal Scale = 1:3,000

DECEMBER 2023

CROSS-SECTION B-B'

Figure No. 4B





LEGEND



MECP WELL RECORD
PROPERTY BOUNDARY

Scale = 1:15,000

MARCH 2022

MECP WELL LOCATION PLAN



Table 1: Summary of Nearby Domestic Water Supply Wells

MECP Well ID	Address	Approximate Distance From Site (m)	Lot	Conc.	Easting	Northing	Township	County/ Municipality	Well Use	Bedrock/ Overburden	Depth to Bedrock (m)	Total Depth of Well (m)	Static Water Level (m)	Year Drilled
	Onsite Domestic Well													
2506888	382063 Concession Road 4	-	22	5	505234	4894764	Bentinck	Grey / West Grey	Domestic / Livestock	Overburden	N/A	25.0	5.5	1980
					R	Registered Wo	ells on Neighb	ouring Propertion	es					
2507455	422102 Concession Road 6	390	23	6	505310	4896060	Bentinck	Grey / West Grey	Public Supply	Bedrock	29.6	61.0	0.9	1981
2502709	133889 Allan Park Road	390	21	6	504450	4895670	Bentinck	Grey / West Grey	Domestic	Bedrock	19.2	24.4	4.6	1968
2516925	382145 Concession Road 4	500	24	5	505840	4895170	Bentinck	Grey / West Grey	Domestic	Bedrock	22.3	29.6	17.7	2006
2516461	133789 Allan Park Road	325	21	5	504680	4894720	Bentinck	Grey / West Grey	Domestic	Bedrock	19.5	29.9	4.6	2005
2516469	133805 Allan Park Road	320	21	5	504680	4894780	Bentinck	Grey / West Grey	Domestic	Bedrock	16.2	29.9	3.7	2005
2516963	133789 Allan Park Road	360	21	5	504650	4894680	Bentinck	Grey / West Grey	Domestic	Bedrock	19.8	41.5	4.0	2006
2512309	382094 Concession Road 4	320	23	4	505620	4894420	Bentinck	Grey / West Grey	Domestic	Bedrock	13.4	34.4	15.2	1993
						Inferred Wel	ls on Neighbo	uring Properties	3					
-	133873 Allan Park Road	390	21	6	504460	4895500	Bentinck	Grey / West Grev	Domestic					
-	133859 Allan Park Road	370	21	5	504500	4895340	Bentinck	Grey / West Grev	Domestic					
-	133776 Allan Park Road	470	20	5	504560	4894550	Bentinck	Grey / West Grev	Domestic					
-	382007 Concession Road 4	340	21	5	504690	4894560	Bentinck	Grey / West Grey	Domestic		No II	nformation		
_	382048 Concession Road 4	230	22	4	505150	4894385	Bentinck	Grey / West Grey	Domestic					
	382064 Concession Road 4	380	22	4	505410	4894280	Bentinck	Grey / West Grey	Domestic					



Table 2:
Onsite Groundwater Elevation Measurements

Well ID	MECP Well ID	Ground Surface Elevation	Top of Pipe [TOP] Elevation	Top of Casing [TOC] Elevation	23-Fe	eb-21	7-Ap	r-21	30-Jı	ın-21	24-M	ar-22	27-0	ct-23	10-A _l	or-23	15-Jı	un-23
		(masl)	(masl)	(masl)	(mbTOP)	(masl)	(mbTOP)	(masl)	(mbTOP)	(masl)	(mbTOP)	(masl)	(mbTOP)	(masl)	(mbTOP)	(masl)	(mbTOP)	(masl)
BH-1 / MW-1	A316371	290.48	291.50	291.61	-	-	2.58	288.92	2.97	288.53	2.11	289.39	2.59	288.91	2.05	289.45	3.01	288.49
BH-2 / MW-2	A316370	295.69	296.76	296.89	-	-	5.65	291.11	6.24	290.52	5.51	291.26	5.35	291.41	5.15	291.61	6.12	290.64
BH-3 / MW-3	A316368	288.44	289.49	289.53	2.31	287.18	1.99	287.50	2.14	287.36	1.48	288.01	1.75	287.74	1.54	287.95	2.05	287.44
BH-4 / MW-4	A316369	296.6	297.67	297.76	8.21	289.46	7.57	290.10	8.08	289.59	7.49	290.18	7.85	289.82	7.41	290.26	7.91	289.76
Onsite Supply Well	2506888		-	295.94	-	-	-	-	6.23	289.71	-	-	-	-	-	-	-	-

Note: The groundwater elevations measured on April 10, 2023 are considered to be the annual maximum groundwater table elevation for the Site, measured following significant snow melt and precipitation.



APPENDIX A: MECP WELL RECORDS



Latitude:44.20903, Longitude:-80.92240 (UTM Zone:17, Easting:506200, Northing:4895093)

Show					Search:	
100						
entries						
Well ID *	Well Record Information	Well Tag # (since 2003)	Audit#	Contractor Lic# °	Well Depth (m) °	Date of Completion (MM/DD/YYYY)
2506888	PDF HTML	N/A	N/A	1804	25.0	06/04/1979
2516461	PDF HTML	A025024	Z25412	2576	29.9	07/14/2005
2516469	PDF HTML	A025018	Z25420	2576	29.9	08/05/2005
2516925	PDF HTML	A043279	Z48391	6634	29.6	07/27/2006
2516963	PDEIHTML	A043695	Z25363	2576	41.5	07/04/2006

8

MINISTRY OF THE ENVIRONMENT COPY


MINISTRY OF THE ENVIRONMENT The Ontario Water Resources Act

414/24

FORM 7 MOE 07-091

WATER WELL RECORD

2506888 1. PRINT ONLY IN SPACES PROVIDED
2. CHECK X CORRECT BOX WHERE APPL 25002 LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS) DEPTH - FEET GENERAL DESCRIPTION ACK TOPSOLL GRAVEL & STONES BROWN SAND GRAVEL & STONES 000/80211 0062611/21 0082628111/2 10 14 15 54 54 55 WATER RECORD 51 **CASING & OPEN HOLE RECORD** WATER FOUND AT - FEET KIND OF WATER DEPTH - FEET FRESH 3 T SULPHUR 2 SALTY 2 [] GALVANIZED
3 [] CONCRETE 3 SULPHUR
4 MINERAL 0082 61 **PLUGGING & SEALING RECORD** SALTY OPEN HOLE STEEL MATERIAL AND TYPE (CEMENT GROUT, LEAD PACKER, ETC.) FRESH
SALTY 3 | SULPHUR
4 | MINERAL 2 GALVANIZED
3 GONCRETE 1 | FRESH 3 SULPHUR 4 🗌 OPEN HOLE 27.30 2 SALTY 4 MINERAL 1 C STEEL 18-21 2 [] GALVANIZED 1 FRESH 3 SULPHUR
2 SALTY 4 MINERAL 3 CI CONCRETE 26-29 30-33 LOCATION OF WELL IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE 2000 7 OF WELL ☐ SHALLOW A DEEP 400 WATER SUPPLY S ABANDONED, INSUFFICIENT SUPPLY FINAL 2 OBSERVATION WELL
3 TEST HOLE
4 RECHARGE WELL **STATUS** 7 🗌 UNFINISHED OF WELL Lot 22 1 M DOMESTIC 2 M STOCK $\overline{\mathcal{V}}$ 6 MUNICIPAL WATER 3 | IRRIGATION PUBLIC SUPPLY USE /2 INDUSTRIAL COOLING OR AIR CONDITIONING ☐ OTHER 9 D NOT USED CABLE TOOL 6 BORING **METHOD** 2 ROTARY (CONVENTIONAL)
3 ROTARY (REVERSE) 7 DIAMOND 8 D JETTING ROTARY (AIR) **DRILLING** 59-62 DATE RECE**2** 0 08 7 9 OFFICE USE ONLY 1804 INSPECTOR W١ CSS.S8



(V) Or	ntario	Ministry of the Environment	Well Tag Number (Place's		nt number below)∗∜	Regulation 903	Ontario	Well R	
	est to establish				y sylven filoso		Ontani		of
	for Complet	. —	s document is a permar	ont logs	I document D	_, a main e a de a a de a de la dela de	a refere		Y;
 All Section 	ons must be co	impleted in full to avo	id delays in processing.	Further	instructions and	d explanations are ava	iilable o	n the back of	this form.
QuestionAll metro	is regarding co e measureme r	mpleting this applicat	ion can be directed to that to 1/10 th of a metre. —	ne Water	Well Manager	and the second		5-6203.	·
	rint clearly in b	lue or black ink only.		MUN		Ministry Use	Only	LOT	
	1 - 1 - f 1 - 1		Mall Information	MON				LOT	
- 4	1 1 m	(y/District/ividificipality)	1000	annp	مسلفان		21	Concession	
RR#/Street Nu	mber/Name	-74CO	Cit	⇒んて、 r/Town/V	illage		•	⊥ S Block/Tract et	C.
GPS Reading		one Easting	Northing Ur	nt Make/M	lodel Mode	e of Operation:	ifferentiate	ed Aver	aned
	8 3	504647	4894688	il ividito/iv	IVIOGO		rentiated,		
		Bedrock Materials (See instructions) Other Materials	1 .25	Conors	al Description		Depth	Metres
General Colour	Most commo		Other Materials	<u> </u> 	Genera	: Description		From	To
0 - 1	TOP 501				<u> </u>			ig.	Sort
BROWN	SANO	620,		<u> </u>	·	and the second s		Sout	6527
bred	Signo Limitstonia	Ro.s.	w CLAH		3			65CL	Jort
*	LINIFYTONE		N Limestows	Lunie	45.			JOLL	1360
		/							
					.*		-		
									:
*									
	Diameter etres Diameter	1	Construction Record		Metres	Pumping test method	t of We	· · · · · · · · · · · · · · · · · · ·	Recovery
From	To Centimetre	#I viairi	UIICKIIESS	Depth		loul			Water Level Metres
0 13	36ct 6"	centimetres	centimetres	From	То	Pump intake set at -		Metres min	ivietres
		Steel	Casing Fibreglass			(metres)3011- Pumping rate -	Level 1	3.20- 1	134
			Concrete · 188	254	7551	(litres/min) OG/W			
Water found at Metres	r Record Kind of Water	Galvanize				Duration of pumping hrs + min	2	2	
			Fibreglass Concrete			Final water level end of pumping umetres	3	3	
Gas Other:	Fresh Sulphu Salty Minera	Galvanize	ed			Recommended pump	4	4	
125 Flm. W	Fresh 🔛 Sulphu		Fibreglass			shallow Deep			
Gas Other:	Salty Mineral	g Plastic Galvanize	Concrete ed			Recommended pump depth. metres	5	5	
	Fresh Sulphu	11	Screen		: '	Recommended pump rate.		10	
Gas U	Salty Minera	-III diam	Fibreglass Slot No.			(litres/min) If flowing give rate -	15 20	15 20	
After test of wel	l yield, water was	6 Plastic Galvanize	Concrete ed	150	1367	(litres/min)	25	25	
Other, speci			No Casing or Scree	<u> </u>		If pumping discontin- ued, give reason.	30 40	30	
Chlorinated 💽	Yes No	Open hol	e			11	50	50	
		Seline Beard	Annular space Abar	Manmant				3.2 60	
Depth set at - Me		ype (bentonite slurry, neat o	ement slurny) etc Volume I		In diagram below	Location of well fr		lot line, and bu	uilding.
	ich Gans	-	(cubic m	erres)	Indicate north by		_		11
		1					X	133794	T.M
:					Los	170 10721	. † 12		
							01	v	
		Mothed of Committee	lan				1		
Cable Tool	√ Kotar	Method of Construct		igging	- Constitution		<u>Z. </u>		-
Rotary (conve	, <u></u> p.,	· =	Jetting O	ther		Con	av.	() C	
	SO/ DOM	Water Use	Diving						
Omestic Stock	☐ Indus		Public Supply	ther				,	
Irrigation	Munic	cipal 🔲	Cooling & air conditioning		Audit No. 7	25363 Dat	e Well C	YYYY	MM DD
Water Supply	Recharge	Final Status of Well	II Unfinished ☐ Abandone	d, (Other)	Was the well ov	77.	2006 e Delivere)	MM DD
Observation v	vell 🗌 Abandone	d, insufficient supply 🔲 I	Dewatering Replacement well		package delivere	in Sala	7006		07 104
rest ⊟ole		ntractor/Technician I				Ministry Use		.	
Name of Well Co	ontractor	et were	Well Contractor's Lice	nce No.	Data Source	Col	ntractor	257	6
Business Addres	s (street name, nur	nber, city etc.)	• • •		Date Received	YYYY MM DD Dat		ection YYYY	MM DD
	chnician (last name		Well Technician's Lice	ence No.	OCT 2 7	2006 We	II Record	Number	<u> </u>
Signature of Tac	hnician/Contractor	bel	Date Submitted YYYY	MM ==	AR LIF	ies at		y P*	
x und	كس	·	2006	M 10	-	-400 GM			
0506E (09/03)	-	Contractor's Co	opy Ministry's Copy	Well Ow	ner's Copy 🗌	Cette fo	ormule e	st disponible	en français

	linistry of Well T	A 043		Regulation 903 Ontari	Well Ro	
All Sections must be com	f Ontario only. This docu pleted in full to avoid dela pleting this application car s shall be reported to 1/1 e or black ink only.	ys in processing. F n be directed to the Oth of a metre.	nt legal document. P curther instructions an Water Well Manage	lease retain for future refered explanations are available of ment Coordinator at 416-23 Ministry Use Only	ence. on the back of t	of this form.
RR#/Street Number/Name GPS Reading NAD Zone		City/	Town/Village Make/Model Mod	Site/Compartment/	ed Wera	
8 3 1 1 2 2 2 2 2 2 2 2	drock Materials (see in	structions) Materials		al Description	Depth From	Metres To J FT
	Limes	O'RAVEL STOWE			73	97 FT.
Hole Diameter Depth Metres Diameter	Co	nstruction Record	Depth Metres	III amping toot moment	v Down R	ecovery
From To Centimetres 20 73 9,201 73 97 6,201 Water Record Water found at Metres Kind of Water Gas Salty Minerals Other: Gas Salty Minerals Other: Mineral	diam centimetres Steel	thickness centimetres Casing ass te ./88	From To O 75F7	Pump intake set at - Static (metres) A, 2 97 Level Pumping rate (tres/min) Duration of pumping 2	/ater Level Time min 5877 63 1	Water Level Metros 70 FT 65 60 58
m Fresh Sulphur Gas Salty Minerals Other: After test of well yield, water was Clear and sediment free Other, specify Chlorinated Yes No	Outside diam Steel Fibregle Galvanized N		75 97FT	Recommended pump rate. (Hitres/min) 15 If flowing give rate - 20 (litres/min) 25 If pumping discontinued, give reason. 40 50 60	10 15 20 25 30 40 50 60	
From To	aling Record Anne (bentonite slurry, rieat cement slurry) AC CROUT Slue BS 3/8 /blephy	urry) etc. Volume Pl (cubic me	onment aced In diagram belo	Location of Well bw show distances of well from road by Low C	l, lot line, and bu	7
Cable Tool	water Use Driving	Oth	HANOXER	48391 Date Well		Suestar ————————————————————————————————————
Test Hole Abandoned, Well Con Name of Well Contractor	ell Unfinish insufficient supply Dewater poor quality Replace tractor/Technician Inform (/CSTme Shark er, city etc.)	ment well ation Well Contractor's Licen A S S S S S S S S S S S S S S S S S S S	package delive Data Source Date Received Remarks	wwner's information red? Yes No Date Deliver Ministry Use Only Contractor	663	
0506E (09/03)	Contractor's Copy	Ministry's Copy	Well Owner's Copy	Cette formule	est disponible	en français

	Ministry of ne Environment	Well Tag	Number (Place	e sticker and print	number below)]			Recor
		A	0250	18		Regulation 903) Ontari		ge of _
nstructions for Completing • For use in the Province o	of Ontario only. Th	is docume	nt is a perm	anent legal	document. Pl	่ lease retain for futur	e refer	ence.	
 All Sections must be com Questions regarding comp 	pleted in full to avo	oid delavs	in processin	ig. Further in	structions and	d'explanations are ava	ailable c	on the bac	k of this for
 All metre measurements 	shall be reported	d to 1/10 th	of a metre.	tile vvater v	Veli Managei				
Please print clearly in blue			FOOT	MUN	C	Ministry Use	∌ Uniy	TTL	ОТ
Vell Owner's Information a	and Location of	well intol	mation		(0)	* DD 1 0			
R#/Street Number/Name	177			City/Town/Vill		Site/Compa			
GPS Reading NAD Zone	e Easting.	North	ing	Unit Make/Mo	del Mode	e of Operation: Und	differentiat	led 🔽	Averaged
GPS Reading NAD Zons 8 3 7 7 Log of Overburden and Be			94777	MERIDI	av	Diffe	erentiated	i, specify	FEE
eneral Colour Most common r		Other Mat			Genera	al Description		Depth	n Metre
our SAND		~ DERS				•		Fron	3/
our SAND	7,304	C NEW 3	1					31	
Y LIMESTON	Æ							53	98
					N.				
		1							
			,						
Hole Diameter		Const	ruction Rec	ord] Tes	et of Wr	ell Yield	
Depth Metres Diameter	Inside	00113	Wall	Depth	Metres	Pumping test method	Draw	w Down	Recovery
From To Gentimetres	diam Mat	erial	thickness centimetres	From	То	AZR	Time W	Vater Level	Time Water L min Metre
0 98 6"	Certamenes		Casing			Pump intake set at - (metres)	Static	12FT	
	Steel	Fibreglass				Pumping rate -	1		1
	•	Concrete	.188	2	55	(litres/min) 3 Company Duration of pumping	2		2
ater found Metres Kind of Water	Galvaniz	Fibreglass				hrs +	1		
n Presh Sulphur	Plastic	Concrete				Final water level end of pumping metres	3		3
Gas Salty Minerals Other:	Galvania					Recommended pump type.			4
m Presh Sulphur	□ Plactic □	Fibreglass				Shallow Dee			5
Other: Salty Minerals	Galvaniz					depth. 60 netres	S		
m Fresh Sulphur			Screen			Recommended pump rate.	10		10
Gas Salty Minerals Other:	diam	Fibreglass Concrete	Slot No.			If flowing give rate -	20		20
er test of well yield, water was Clear and sediment free	Galvania					(litres/min) If pumping discontin-	25 30		30
Other, specify		No C	asing or Scr	een		ued, give reason.	40		40
hlorinated Yes No	Open ho	ole		55	98		50 60		50 60
Plugging and Se	aling Record	Annula	rspace	bandonment		Location			
Depth set at - Metres Material and type	pe (bentonite slurry, neat		Volur	ne Placed ic metres)	In diagram belo	w show distances of well			nd building.
O 30 GRO	UT		(000	, met. 907	AN	y arrow.			
						1	-		- -
		<u></u>				Page V	50	7	^
							I O		
	Method of Construc	ction				ALLAN A	0		
Cable Tool Rotary	(air)	Diamond	Ę	Digging			-		
Rotary (conventional) Air perd Rotary (reverse) Boring] Jetting] Driving		Other		LED SOFT 4	TH C	Cow	
	Water Use	1 D. I. II. O		Other	4" PLAS				
Domestic Industri Stock Comme	ercial] Public Supp] Not used				INER	-4- 10/-11	Campleted	
☐ Irrigation ☐ Municip	Final Status of W		ir conditioning		Audit No. Z	25420	are Aveil	200°	5 080
Water Supply Recharge w		Unfinished	_	loned, (Other)	Was the well of package deliver	Wilei 3 Illioithadoit	ate Delive	ered Y	YYY MM
Test Hole Abandoned,	, insufficient supply , poor quality	Replaceme	nt well		puonage deliver		ec 0=1-		
Well Con Name of Well Contractor	ntractor/Technician	Information W	on ell_Contractor's	Licence No.	Data Source	Ministry U	ontractor	· ·	C
HIGHLAND WA	TER WELL	s "	25 76		Doto Bassina		Z late of lat	57	0
Business Address (street name, numb	ber, city etc.) H <i>A</i> カー <i>O</i> ルT	- N	06 11	RO	Data Received	8 2005 I	ate Of INS	spection Y	YYY MM
lame of Well Technician (last name,	first name)	<u> </u>	ell Technician's	dicence No.	Remarks L	TETED	/ell Reco	ord Number	
Signature of Federal Contractor		Da	te Submitted		AT 20	10.6.P.M.			
X 0506E (09/03)	Contractor's				ner's Copy 🗌	Cette	formule	est dispo	nible en frar
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Contractor s			,	لسا راءرا		•	•	
						The state of the s			AND SELECT SEA AND SERVICE OF THE SERVICE OF

B	7) (ont	ario		/ linistry of le Enviror	nment	Well Tag	Number (Pla	nce sticker and print	number below)	1	903 Ontari	Well	Record esources Act
Ins	truction	ons fo	or Con	npleting	g Form		1	90250	024	``	_		pag	e of
. •	For u	se in tl	he Pro must	vince o	f Ontario	only. This	s docume	ent is a pern in processi	nanent legal ng. Further ir	document. P	Please retain for	uture refer	ence. on the back	of this form.
•	Ques	tions r	egardii	ng comp	leting this	s applicati	on can b	e directed to	o the Water \	Vell Manage	ment Coordinato	r at 416-23	5-6203.	
•	Pleas	e print	t clearl	y in blue	or black	ink only.		FOUT	MUN		Ministry	Use Only		т
, F														
Add	iress of			• • •	District/Mu				ownsnip			7 1	Concess	ion _
RR#	#/Street		er/Nam		UNT'	Y		<	SE ルイエ City/Town/Vill		Site/Co	mpartment/		t etc.
GPS	S Read	ing	NAD	Zone	Eastin	16/15	North	95026	Unit Make/Mo	del Mod	e of Operation:	Undifferentiated		veraged
			ırden	and Be	drock Ma	aterials (see msi	ructions	1 12 1 2 2 2				Depth	FEET
	eral Co			common r	naterial	Pa.	Other Ma			Gener	al Description		From	70 21
BRO			SAI Sai			1304	LDER	<u>{ 7</u>	u	JET			21	58
GRE	Y	(, ,RA	UEL		5A	ND					,	58	64
GR	ξY	4	TH	ESTO	NE								64	98
	-													
		ole Dia					Cons	truction Rec	ord			Test of We	ell Yield	Recovery
	epth rom	Metro		ameter timetre s	Inside diam	Mate	rial	Wall thickness	Depth	Metres	Pumping test me		/ater Level T	ime Water Level
	0	98	3	6"	centimetres	. Ar salya No		centimetres Casing	From	То	Pump intake set a		4	IIII WOLGS
					10	Steel	_	.188	1	65	Pumping rate - (litres/min) 25	1		1
		ater R			6"	Plastic Galvanize	Concrete	.100	2	0.5	Duration of pump	ng 2		2
at LX	ter found Metre	es Fre	Kind of '	Water Sulphur			Fibreglass Concrete				Final water level of pumping			3
	Gas Other:	U Sal	TES	Minerals TEB		Galvanize	ed				Recommended p	<i>→</i>		4
9	5 m Gas	Fre		Sulphur Minerals]Fibreglass]Concrete				Shallow Recommended p	Deep ump 5		5
	Other:		7 ,-	 .		Galvanize	ed	Screen	1		Recommended p	ump 10	,	10
	Gas **** Other:	Sa		Sulphur Minerals	Outside diam	Steel	Fibreglass	Slot No.			rate. (littee/still) If flowing give at	4 15 e - 20		15 20
Afte	er test o		eld, wate			Plastic Galvanize	Concrete ed		-		(litres/min)	25		25
	Other,		/				No C	asing or Sc			ued, give reason.	40		40
Chi	lorinated	d V Ye	s 🗌	No		Open hol	e		65	98		50 60		50 60
De	enth set a	Pl at - Metre			aling Rec		Annula	- 	Abandonment ime Placed	In diagram belo	Locat ow show distances of	ion of Well		d building.
	From	30	Iviate	rial and typ	·	slurry, neat o	ement sturry	(cut	oic metres)	Indicate north	by arrow.			
		3)		7701							GTH CON			
			_								5	•		
											ROSO	651	<u>1 X</u>	·
	Cable To	ool	[Notary (Diamond		Digging		2 2	1/2	>	
[' '	conventi reverse)	, -	Air perd Boring			Jetting Driving	_	Other		, N	1002		·
	Domesti	ic		Industria		er Use	Public Sup	ply	Other	4	THOON			
	Stock Irrigation	n]]	Comme Municip	al			air conditioning		Audit No. 7	25412	Date Well	Completed	AID PE
I	Water S	Supply	Re	echarge w			Unfinished	_	doned, (Other)	Was the well	owner's information	Date Delive	ered YYY	
	Observa Test He	ation wel	At	oandoned,	insufficient poor quality		Dewatering Replaceme	ent well		package delive		y Use Only	,	
		ell Cont	ractor			chnician	V	/ell Contractor's	s Licence No.	Data Source		Contractor		3
Bu	siness A	HLA ddress (street na	ame, numb	er, city etc.)	NELLS		25 7 OG 1		Date Received SEP	U D SUUE I	D-1	pection YY	
Na	me of W	ell Tech	nician (la	ast name,	first name)	ONT		/ell Technician		Remarks	08 2005 LIFTEO	Well Reco	rd Number	19pm
Sig	nature o	HA Toello	ician/Co		//		Da	ate Submitted	XY O'T IPE	AT Q	LIFTED 200+G.P.N	1.	- • · - •	▼
05	06E (09/0	03)			Co	ntractor's C	opy 🔲 1		y ☐ Well Ow	ner's Copy		ette formule	est dispon	ible en français



The Ontario Water Resources Act WATER WELL RECORD

Environment Ontario 1. PRINT ONLY IN S	PACES PROVIDED CT BOX WHERE APPLICABLE	2512309	104
COUNTY OR DISTRICT	TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE	CON BLOCK, TRACT, SURVEY ETC	LOT 25-27
7 3 112 1 7	BENTINC	DATE COMPLETED	09" 00
	KK#3	ELEVATION RC BASIN CODE II	10 07 YR 23
1 2 M 10 12	17 18 24 25	26 30 31	42
LO	G OF OVERBURDEN AND BEDROC	K MATERIALS (SEE INSTRUCTIONS)	
GENERAL COLOUR COMMON MATERIAL	OTHER MATERIALS	• GENERAL DESCRIPTION F	ROM TO
	GRAVEL		0 30
	CLAY OGRAVEL		30 44
GREY	Roc K		44 80
BROWN	Rock		30 113
//1)			-
31			1, 1, 1, 1, 1
32			ا لیلیلیا
41 WATER RECORD	51 CASING & OPEN HOLE RI	ECORD SIZES OF OPENING SI-33 DIAMETER	34-38 LENGTH 39-4
WATER FOUND AT - FEET KIND OF WATER	INSIDE WALL DE DIAM MATERIAL THICKNESS FRUI	C MATERIAL AND TYPE	INCHES FEE H TO TOP 41-44
80 10-13 1 RESH 3 DSULPHUR 14 DMINERALS 6 DGAS	10-11 1 GSTEEL 12 2 GALVANIZED 1.88 0	13-16	FEET
TO 15-18 FRESH 3 DSULPHUR 19	3 CONCRETE 4 OPEN HOLE 5 PLASTIC	61 PLUGGING & SEALING	
20-23 1 G FRESH 3 GSULPHUR 24 4 G MINERALS	17-16 1 STEEL 19 2 GALVANIZED 3 CONCRETE	20-23 DEPTH SET AT - FEET MATERIAL AND TYPE FROM TO 10-13 14-17	CEMENT GROUT LEAD PACKER, ETC)
25-28 1 FRESH 3 SULPHUR 29	4 GPPEN HOLE 5 □ PLASTIC 24.75	27-30 16-21 22-25	
30-33 GERSM 3 SULPHUR 34 80	1 USTEEL 2 GALVANIZED	26-29 30-33 80	
2 SALTY 6 GAS	5 PLASTIC		
71 PUMPING TEST METHOD AIR PUMPING RATE	11-14 DURATION OF PUMPING 15-16 SO 17-18 HOURS MINS	LOCATION OF WELL	<u> </u>
LEVEL DIMPING	EVELS DURING 2 A RECOVERY	IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM LOT LINE INDICATE NORTH BY ARROW	ROAD AND
19-21 22-24 15 MINUTES 24-2			
SOFEET 68 FEET 50 EI IF FLOWING. GIVE RATE SB-61 PUMP INTAKE			
TECOMMENDED PUMP TYPE RECOMMENDED PUMP TYPE		}	
SHALLOW DEEP SETTING	85 FEET PUMPING 7 GPM	1	
54	s ☐ ABANDONED, INSUFFICIENT SUPPLY		
STATUS	L 6 ABANDONED POOR QUALITY 7 UNFINISHED	Dell 100	[.
OF WELL 4 PECHARGE WELL	☐ DEWATERING S ☐ COMMERCIAL	mile musex ed	J#4
WATER 2 STOCK 3 IRRIGATION	MUNICIPAL PUBLIC SUPPLY	axe ! !	WI !
USE 4 INDUSTRIAL OTHER		HANDOKER - MUROCK BO	Du
S7 1 GABLE TOOL	6 ☐ BORING		
METHOD OF OF ROTARY (CONVENT REVERSE CONSTRUCTION ROTARY (AIR)			100500
S AIR PERCUSSION	DIGGING OTHER	DRILLERS REMARKS	106592
NAME OF WELL CONTRACTOR	WELL CONTRACTOR'S LICENCE NUMBER	DATE OF INSPECTION DATE OF INSPECTION SE CONTRACTOR 3 4 SEP 2 INSPECTOR	3 1993
RAUTMAN I NUESTA RAUTMAN I NUESTA RAUTMAN & LAMWOO RAUTMAN & JA RAUT		DATE OF INSPECTION INSPECTOR	<u> </u>
NAME OF WELL TECHNICIAN	NOG-ISO WELL TECHNICIAN'S LICENCE NUMBER	O REMARKS	
SIGNATURE OF TECHNICIAN/CONTRACTOR	9CKSON T-1930	GS CS	SS.ES
How I tank	DAY 21 NO. 09 YR25	ō	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

The Ontario Water Resources Act

4/ x/2W

FORM NO. 0506-4-77 FORM 7

VATER WELL RECOR

Environment 2507455 CON 1. PRINT ONLY IN SPACES PROVIDED 25002 2. CHECK 🗵 CORRECT BOX WHERE APPLICABLE # Elmwood LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS MOST COMMON MATERIAL GENERAL COLOUR OTHER MATERIALS GENERAL DESCRIPTION FROM Black Topsoil 0 Larg Bolders clay grave 17 Brown 97 200 Bedrock (3) 32 CASING & OPEN HOLE RECORD 41 WATER RECORD 51 WATER FOUND AT - FEET FRESH 3 SULPHUR
SALTY 4 MINERAL 00 Z [] GALVANIZED 10100 188 0 1 RESH 3 SULPHUR
2 SALTY 4 MINERAL PLUGGING & SEALING RECORD 0200 C) OPEN HOLE FEET 1 [] STEEL 1 FRESH 3 SULPHUR
2 SALTY 4 MINERAL 2 ET GALVANIZED [] CONCRETE 1 | FRESH 1 | SULPHUR 2
2 | SALTY 4 | MINERAL 4 FT OPEN HOLE 27.30 [] STEEL 2 [] GALVANIZED 1 | FRESH 3 | SULPHUR
2 | SALTY 4 | MINERAL [] CONCRETE OPEN HOLI LOCATION OF WELL Waiv. 1 🗍 PUMP IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE ... INDICATE NORTH BY ARROW. STATIC LEVEL ···· 003 **a**3 5+0352 RECOMMENDED PUMP TYPE well 0.55 Km ☐ SHALLOW 💥 DEEP WATER SUPPLY S ABANDONED, INSUFFICIENT SUPPLY FINAL 2 OBSERVATION WELL
3 TEST HOLE 6 ABANDONED POOR QUALITY STATUS / 7 UNFINISHED **OF WELL** 4 | RECHARGE WELL DOMESTIC 5 COMMERCIAL MUNICIPAL
PUBLIC SUPPLY WATER 07 3 | IRRIGATION
4 | INDUSTRIAL COOLING OR AIR CONDITIONING
ONE NOT USED OTHER METHOD Z CABLE TOOL 6 BORING ROTARY (CONVENTIONAL)

TO ROTARY (REVERSE)

ROTARY (AIR)


AIR PERCUSSION 7 DIAMOND DRILLING 9 | DRIVING 250681 RIFRS well Drilling 4544 H5HH Auther OFFICE USE

SUBMISSION DAT

APPENDIX B: BOREHOLE LOGS




Testhole ID: BH-1 / MW-1






Testhole ID: BH-2 / MW-2






Testhole ID: BH-3 / MW-3





Testhole ID: BH-4 / MW-4







Testhole ID: BH-4 / MW-4

MPLE TYPE NUMBER SRAPHIC LOG LOG LOG LOG LOG MAPLE TYPE NUMBER NU	CLIENT _(PROJECT					PROJECT NAME _Hydrogeological Study PROJECT LOCATION _382063 Conc. 4, Bentinck		
		ELEVAT	MPLE TYP NUMBER	=	MATERIAL DESCRIPTION			

Borehole Terminated at 8.74 m.

APPENDIX C: SITE PHOTOGRAPHS

Maximum Predicted Water Table Elevation and Hydrogeological Assessment Report



Photo 1 - View of southern Portion of the Site looking northeast from the southwest corner of the property. MW–3 in front. (March 25, 2022)



Photo 2 - Drilling of MW-4 (February 23, 2021)





Maximum Predicted Water Table Elevation and Hydrogeological Assessment Report



Photo 3 - View of sand and gravel in the location of MW-2.







SAUGEEN VALLEY CONSERVATION AUTHORITY

ONTARIO REGULATION 169/06 DEVELOPMENT, INTERFERENCE WITH WETLANDS AND ALTERATIONS TO SHORELINES AND WATERCOURSES

For the features and areas subject to Ontario Regulation 169/06 permission from the SVCA is required before any person may: *undertake development, straighten, change, divert or interfere in any way with a watercourse, or change or interfere in any way with a wetland*.

"Development" is defined as:

- (a) the construction, reconstruction, erection or placing of a building or structure of any kind,
- (b) any change to a building or structure that would have the effect of altering the use or potential use of the building or structure, increasing the size of the building or structure or increasing the number of dwelling units in the building or structure,
- (c) site grading, or
- (d) the temporary or permanent placing, dumping or removal of any material, originating on the site or elsewhere.

The Following Areas and Features are Subject to the Regulation:


- Hazardous lands including flood plains (based on the Regional Storm Flood, also called the Hurricane Hazel Flood Event Standard), erosion prone lands, and unstable soils.
- Watercourses (including inland lakes).
- Wetlands and areas adjacent to wetlands.
- Valleys and steep slopes (and slope setbacks).
- Lake Huron shoreline (flooding, erosion and dynamic beach hazards).

How to Determine Regulated Areas

- For urban centres (such as Walkerton, Paisley, Kincardine, Durham) and near these areas, SVCA mapping is available at the Authority office showing the Regulations Limits. Contact the SVCA for information about specific properties.
- For all other areas Regulation Mapping is not available; instead a 'screening' method is used to determine potential Regulated Areas. In municipal comprehensive zoning by-laws the "Environmental Protection" (EP) zone (or similar zone such as EH, NE, etc.) generally identifies the features and areas where Regulation 169/06 could apply. But, the EP zone boundary is not intended to be the Regulation Limit. Therefore, the 'screening area' includes the EP zone plus a 50 metre distance beyond the zone boundary; and a 120 metre distance from Provincially Significant Wetlands (Provincially Significant Wetlands are identified in the County Official Plan). For any proposal in the screening area, the SVCA should be contacted. SVCA staff will then determine whether a permit is required and inform the proponent accordingly.
- All watercourses (rivers, creeks, streams, etc.) and wetlands are subject to the Regulation.

Note: This handout is a summary only and for the full text of the Regulation and related information, reference should be made to Ontario Regulation 169/06 and the *Conservation Authorities Act*, R.S.O 1990, Chap. C.27, Section 28.

APF GREY COUNTY OFFICIAL PLAN MAPPING AND INFO	PENDIX E:



- within *Core Areas* or *Linkages*, provided no new residential *dwellings* are permitted on the remnant parcel.
- 9) Where possible, transportation, utility, and service corridors should avoid the *Natural heritage system*, especially *Core Areas* where possible. Transportation, utility, and service corridors include sewage, water and stormwater management systems, electricity transmission and distribution systems (e.g. hydro corridors), communications / telecommunications, transportation corridors, trails, oil and gas pipelines and associated facilities. Such corridors may be subject to the Municipal Class Environmental Assessment process. Where not avoidable, crossing of *Core Areas* and *Linkages* should be minimized, consider the shortest route across the *Core Area* or *Linkage*, and include context *sensitive* design, such as a narrow footprint, eco-passages, and other best management practices.
- 10) Compatible recreation means recreational uses that will not negatively impact the natural features or function of the Core Areas or Linkages and would not be in contradiction of the prohibitions listed above.

7.2 Hazard Lands

Hazard Lands include floodplains, steep or erosion prone slopes, organic or unstable soils, poorly drained areas, and lands along the Georgian Bay shoreline. These lands can be impacted by flooding, erosion, and/or dynamic beach hazards or have poor drainage, or any other physical condition that is severe enough to pose a risk for the occupant, property damage, or social disruption if developed. While these lands are intended to be regulated so as to avoid natural hazards, they also contribute to the natural environment within the *County*.

New *development* shall generally be directed away from *Hazard lands*. The policies of this section of the Plan work together with MNRF Natural Hazards Technical Guidelines, as well as *conservation authority* regulations, and policies.

- 1) The Hazard lands land use types are shown on Schedule A. Hazard lands have not been mapped within the Niagara Escarpment Plan Area within Schedule A. Hazard lands may still exist within the Niagara Escarpment Plan Area and as such it is recommended that consultation occur with the conservation authority and the Niagara Escarpment Commission.
- 2) Permitted uses in the *Hazard Lands land use type* are forestry and uses connected with the conservation of water, soil, wildlife and other natural resources. Other uses also permitted are agriculture, passive public parks, public *utilities* and *resource based recreational uses*. The aforementioned uses will only be permitted where site conditions are suitable and where the relevant hazard impacts have been reviewed.

- 3) In the *Hazard Lands land use type* buildings and structures are generally not permitted. Minor extensions or enlargements of existing buildings and structures may be permitted subject to the policies of Section . 7 Non-habitable buildings connected with public parks, such as picnic shelters, may be permitted.
- 4) Development and site alteration is not permitted within the floodway portion of the floodplain or defined portion of the dynamic beach. The floodway is the entire floodplain, unless the Two-Zone Concept is in use.
- 5) Implementation of the existing Two-Zone Concept or *Floodplain* Special Policy Area is subject to the following:
 - a) The Two-Zone Concept shall continue to be used for the Saugeen River floodplain on Lot 56 to 59 inclusive, Concession 2 E.G.R., (Glenelg Township) Municipality of West Grey, with the floodway being the 100 Year floodplain and the flood fringe being the outer portions of the Regional Storm floodplain. Appropriate development may be permitted in the flood fringe provided suitable flood damage reduction measures are undertaken to protect against Regional Storm flooding. Development and site alteration within the floodway, flood fringe or Regulated Area requires the approval of the conservation authority, in addition to any other applicable approvals.
 - b) Implementation of a new two-zone concept will be done through a municipal official plan amendment
- 6) Placing, removing, or re-grading fill material of any kind, whether originating on the site or elsewhere, is not permitted without written approval of the appropriate conservation authority in Hazard Lands.
- 7) Certain public or private works which, by their nature, must locate within *Hazard Lands* shall be permitted to do so. These works include flood and erosion control, drainage, water works, those directly required for the management or maintenance of the natural environment, and other necessary works of approved design.
- 8) Replacement of existing buildings or structures may be permitted if the hazard risk does not increase from the original condition, and the feasibility of re-locating the buildings or structures outside of the hazard areas has been assessed.
- 9) In the *Hazard Lands land use type development* and *site alterations* will only be considered if all of the following can be satisfied:

- a) The hazards can be safely addressed and new hazards are not created or existing ones aggravated;
- b) No adverse environmental impacts will result. The *County*, in consultation with the *conservation authority*, may require an *environmental impact study* to be prepared at the proponent's expense, in accordance with this Plan;
- c) Vehicles and people have a way of safely entering and exiting at all times;
- d) The development does not include;
 - i. Institutional uses including hospitals, nursing homes, pre-school, school nurseries, day care and schools, where there is a threat to the safe evacuation of the sick, the elderly, persons with disabilities or the young during an emergency as a result of flooding, failure of flood proofing measures or protection works, or erosion; or
 - ii. Emergency services such as that provided by fire, police, and ambulance stations and electrical substations, which would be impaired during an emergency as a result of flooding, the failure of flood proofing measures and/or protection works, and/or erosion; or
 - iii. Involve hazardous substances, and their disposal, manufacture, treatment or storage of.
- e) The advice or approval where required, of the appropriate *conservation* authority shall be obtained. The *County* and the *conservation* authority will consider the mitigation of effects on vegetation, wildlife and fishery resources, and the natural features of the site.
- f) There is no feasible location for the *development* outside of the *Hazard Lands* land use type.
- 10) Where new *development* is proposed on a site, part of which is *Hazard Lands*, then such lands may not be acceptable as part of the five per cent dedication for parkland. All lands dedicated to the municipality shall be conveyed in a condition satisfactory to local municipality.
- 11)Precise delineation of *Hazard Lands* will be shown in the local zoning by-laws. An amendment to the Official Plan will not be required to permit redefining of a Hazard Land boundary. Modifications to the *Hazard Lands* may occur through a zoning by-law amendment after consultation with the *conservation authority* and the approval authority.

7.3 Wetlands

The *County* generally encourages *development* be setback from *Wetlands* by at least 30 metres. In some cases this 30 metres distance can be reduced based on site-specific circumstances, or through the completion of an EIS.